

AMENDMENTS TO THE CLAIMS

Please amend the claims as follows:

1. (Currently amended) A method for writing or reproducing a data to/from an optical recording medium, ~~said-the~~ optical recording medium including a Defect Management Area for managing defective areas, comprising:

determining whether data to be written is real time data;

~~transferring information on~~ specifying defective areas based on information on defective areas listed on the Defect Management Area prior to writing real time data, if the data to be written is real time data;

generating a write command such that the specified defective areas are not allocated to ~~said-the~~ real time data to be written ~~based upon the information on defective areas~~ as a result of the specifying step; and

writing the real time data on the optical recording medium in response to ~~said-the~~ write command.

2. (Previously presented) The method of claim 1, wherein the information on defective areas is positional information of a defective block listed on a Defect List of the Defect Management Area.

3. (Previously presented) The method of claim 2, wherein the information on defective areas is a first sector number of each defective block listed in the Defect List.

4. (Previously presented) The method of claim 2, wherein the information on defective areas retains a logical sector number as is.

5. (Currently amended) The method of claim 1, wherein the information on defective areas is positional information of defective areas listed on a PDL (Primary Defect List) and an SDL (Secondary Defect List), ~~said~~the PDL and SDL being included in the Defect Management Area.

6. (Previously presented) The method of claim 1, further comprising writing file information on a file architecture with reference to the information on defective areas upon completion of real time data recording or during the real time data recording.

7. (Previously presented) The method of claim 1, wherein the write command generated based upon the information on defective areas is a new write command generated based upon information of a defective block.

8. (Previously presented) The method of claim 7, further comprising:

skipping a newly encountered defective block during writing of data in response to one of either the real time write command or the new write command; and

writing data on a next good block subsequent to the newly encountered defective block.

9. (Currently amended) The method of claim 7, further comprising:

terminating one of either the real time write command or the new write command upon a newly encountered defective block, and ~~transferring~~ issuing information on the newly encountered defective block during writing of data in response to one of either the real time write command or the new write command which has been terminated; and

generating a second new write command based upon the information on the newly encountered defective block.

10. (Currently amended) A method for writing or reproducing data to/from an optical recording medium, ~~said~~ the optical recording medium including Defect Management Areas for managing defective areas, comprising:

~~transferring information on~~ specifying defective areas based on information on defective areas listed on the Defect Management Areas prior to writing real time data, if the data to be written is real time data;

generating a write command such that ~~said~~ the real time data is not written on a defective area ~~based upon the information on defective areas~~ in advance as a result of the specifying step;

writing the real time data on the optical recording medium in response to ~~said~~ the write command; and

skipping a newly encountered defective block during writing of data in response to the write command; and writing data on a next good block subsequent the newly encountered defective block.

11. (Currently amended) The method of claim 10, further comprising ~~transferring~~ issuing information on the skipped defective blocks upon termination of the write command to update the information on defective areas.

12. (Currently amended) The method of claim 10, further comprising:

terminating the write command upon a newly encountered defective block and ~~transferring~~issuing information on the newly encountered defective block during writing of data in response to the write command; and

generating a new write command based upon the information on the newly encountered defective block.

13. (Previously presented) The method of claim 12, wherein the information on the newly encountered defective block is a written sector number and a consecutive defective sector number.

14. (Currently amended) The method of claim 10, further comprising ~~writing data on a newly defective block as is, during writing of data in response to the write command~~ file information on a file architecture to specify the written data upon completion of the data recording or during the data recording.

15. (Currently amended) The method of claim 14, wherein the ~~file control~~ information ~~written out for a file~~ is separated by the defective areas based upon on the information on defective areas.

16. (Canceled)

17. (Canceled)

18. (Currently amended) A method for writing or reproducing a data to/from an optical recording medium, ~~said the~~ optical recording medium including Defect Management Areas for managing a defective areas, comprising:

~~transferring the information on specifying~~ defective areas based on information on defective areas listed on the Defect Management Areas in order to write data on an area of the optical recording medium ~~in response to said information on~~ as excluding the defective areas, if data to be written is real time data;

generating a write command such that ~~said the~~ real time data is not written on a defective area ~~based upon the information on the defective areas in~~ advance as a result of the specifying step;

writing the real time data on the optical recording medium in response to ~~said the~~ write command; and

writing data on a newly encountered defective block as is; during writing of data in response to the write command.

19. (Currently amended) The method of claim 18, further comprising ~~transferring~~ issuing information on the newly encountered defective blocks upon termination of the write command to update the information on defective areas.

20. (Currently amended) The method of claim 18, further comprising:
terminating the write command upon a newly encountered defective block and ~~transferring~~ issuing information on the newly encountered defective block during writing of data in response to the write command; and
generating a new write command based upon the information on the newly encountered defective block.

21. (Previously presented) The method of claim 20, wherein the information on the newly encountered defective block is a written sector number and a consecutive defective sector number.

22. (Currently amended) The method of claim 18, ~~wherein file structure information written out for a file is separated by the defective areas based upon the information on defective areas~~ further comprising writing file information on a file architecture to specify the written data upon completion of the data recording or during the data recording.

23. (Canceled)

24. (Previously presented) The method of claim 18, wherein the information on the defective areas retains a logical sector number as is.

25. (Previously presented) A method for writing or reproducing a data to/from an optical recording medium, ~~said the~~ optical recording medium including Defect Management Areas for managing defective areas, comprising:

~~transferring information on~~ specifying defective areas based on information on defective areas listed on the Defect Management Areas in order to write data on an area of the optical recording medium ~~in response to said information on~~ as excluding the defective areas, if data to be written is real time data;

generating a write command such that ~~said~~the real time data is not written on a defective area ~~based upon the information on defective areas~~ as a result of the specifying step;

writing the real time data on the optical recording medium in response to ~~said~~the write command; and

performing one of writing data on a newly encountered defective block as is, or skipping the newly encountered defective block during writing of data in response to the write command.

26. (Previously presented) The method of claim 25, further comprising, writing data on a next good block subsequent to the newly encountered defective block if the newly encountered defective block is skipped in the performing step.

27. (Previously presented) The method of claim 24, further comprising, writing file information on a file architecture with reference to the information on defective areas upon completion of real time data recording or during the real time data recording.

28. (Previously presented) The method of claim 27, wherein the information written out for a file is separated by the defective areas based upon the information on defective areas.

29. (Currently amended) A method for writing or reproducing a data to/from an optical recording medium, ~~said~~the optical recording medium including Defect Management Areas for managing defective areas, comprising:

(a) ~~outputting information identifying on~~ defective areas based on information on defective areas listed on the Defect Management Areas in advance prior to writing data in real time;

(b) generating a write command such that the defective areas are not allocated to a data area to be written ~~based upon the information on the defective areas output from~~ in advance as a result of the step (a); and

(c) writing the real time data on the optical recording medium in response to ~~said~~the write command.

30. (Previously presented) The method of claim 29, wherein the information on defective areas is positional information of a defective block listed on a Defect List of a Defect Management Area.

31. (Previously presented) The method of claim 30, wherein the information on defective areas is a first sector number of each defective block listed in the Defect List.

32. (Previously presented) The method of claim 30, wherein the information on defective areas retains a logical sector number as is.

33. (Previously presented) The method of claim 29, further comprising writing file information on a file architecture with reference to the information on defective areas upon completion of the data recording or during the data recording.

34. (Previously presented) The method of claim 29, wherein the write command generated based upon the information on defective areas is a new write command generated based upon information of a defective block.

35. (Previously presented) The method of claim 34, further comprising:
skipping a newly encountered defective block during writing of data in response to one of either the write command or the new write command; and

writing data on a next good block subsequent to the newly encountered defective block.

36. (Currently amended) The method of claim 34, further comprising:

terminating one of either the write command or the new write command upon a newly encountered defective block, and ~~transferring~~ issuing information on the newly encountered defective block during writing of data in response to one of either the write command or the new write command which has been terminated; and

generating a second new write command based upon the information on the newly encountered defective block.

37. (Previously presented) A method for writing or reproducing data to/from an optical recording medium, ~~said optical recording medium including Defect Management Areas for managing defective areas,~~ comprising:

(a) ~~outputting information on~~ identifying defective areas based on positional information on defective areas listed on the a Defect Management Areas List in advance prior to writing data in real time;

(b) generating a write command to exclude the defective areas from an area allocation for the data writing in advance based ~~upon the information on defective areas output from~~ on the step (a); and

(c) writing the data on the area of the optical recording medium in response to said ~~the~~ write command.

38. (Currently amended) The method of claim 37, wherein the positional information on the defective areas is a first sector number of each defective block listed in a ~~the~~ Defect List of the a Defect Management Areas Area.

39. (Currently amended) The method of claim 37, wherein the positional information on the defective areas retains a logical sector number as is.

40. (Currently amended) The method of claim 37, further comprising writing file information on a file architecture with reference to the positional information on the defective areas upon completion of the data recording or during the data recording.

41. (Previously presented) The method of claim 40, wherein the file information includes a size of recorded data and/or start address of the recorded data.

42. (Currently amended) A method for writing or reproducing data to/from an optical recording medium, ~~said optical recording medium including Defect Management Areas for managing defective areas,~~ comprising:

(a) outputting information on defective areas listed on ~~the~~ a Defect Management Areas List ~~in advance~~ prior to writing real time data;

(b) receiving a write command ~~to exclude~~ excluding the defective areas from an area allocation for real time data in advance based upon the information on defective areas output from the step (a); and

(c) writing the real time data on the optical recording medium in response to ~~said~~ the received write command.

43. (Previously presented) The method of claim 42, wherein the information on defective areas is a first sector number of each defective block listed in a Defect List of a Defect Management Area.

44. (Previously presented) The method of claim 42, wherein the information on defective areas retains a logical sector number as is.

45. (Previously presented) The method of claim 42, further comprising writing file information on a file architecture with reference to the information on defective areas upon completion of real time data recording or during the real time recording.

46. (Previously presented) The method of claim 45, wherein the file information includes a size and/or a start address of the recorded data.

47. (Currently amended) A method for writing or reproducing data to/from an optical recording medium, ~~said optical recording medium including a Defect Management Area for managing defective areas, comprising:~~

- (a) determining whether to write data in real time; and
- (b) controlling a write mode such that the data to be written in real time is written on an area of the optical recording medium as excluding the defective areas listed in the a Defect List Management Area ~~from an area to be written in advance~~ before the actual writing of the data, if the data is determined to be written in real time.

48. (Currently amended) The method of claim 47, wherein the information on defective areas is a first sector number of each defective block listed in ~~a~~ the Defect List of the, wherein the Defect List is included in a Defect Management Area.

49. (Previously presented) The method of claim 47, wherein the information on defective areas retains a logical sector number as is.

50. (Currently amended) The method of claim 47, further comprising, writing file information on a file architecture ~~with reference to the information on defective areas to specify the written data~~ upon completion of data recording or during the data recording.

51. (Currently amended) The method of claim 50, wherein the file information includes a size and/or a start address of the ~~recorded~~ written data.

52. (Currently amended) A method for writing or reproducing a data to/from an optical recording medium, ~~said optical recording medium including a Defect Management Area for managing defective areas,~~ comprising:

(a) determining whether data is provided in real time; and

(b) controlling a write mode such that data provided in real time is written on an area of the optical recording medium, by specifying and excluding the defective areas listed in the a Defect List Management Area from an area to be written in advance before the actual writing of the data, if the data is provided in real time.

53. (Currently amended) An optical recording medium, comprising:

(a) a Defect Management Area for managing defective areas; and

(b) a data area ~~including at least one defective area~~ where data is written; and

(c) ~~a spare area for replacing the defective areas of the data area,~~ wherein information the data is written according to a write command, the write command being generated by referring to on the defective areas is reported in advance before real time recording so as to exclude the defective areas when the real time data is recorded on the optical recording medium, ~~while the defective areas are not replaced with a replacement block of spare area during~~

the real time recording wherein the defective areas are specified based on information stored in the Defective Management Area.

54. (Currently amended) The optical recording medium of claim 53, further comprising ~~(d)~~ (c) a file system information for ~~managing~~ specifying the data recorded on the recording medium.

55. (Previously presented) The optical recording medium of claim 54, wherein the file system information includes supplementary information indicating at least a size of the data recorded, the supplemental information being written with reference to the defective areas.

56. (Previously presented) The optical recording medium of claim 55, wherein the supplementary information is written excluding the defective areas.

57. (Previously presented) The optical recording medium of claim 55, wherein the supplementary information further indicates the start address of the recorded data.

58. (Previously presented) The optical recording medium of claim 54, wherein the file system information is recorded upon completion of the data recording or during the data recording.

59. (Currently amended) An optical recording medium, comprising:

- (a) a Defect Management Area for managing defective areas;
- (b) a data area including defective areas where data is written,
- (c) a spare area for replacing ~~the~~ at least some defective areas ~~of included~~ in the data area; and
- (d) a file system information area for managing recorded data, the file system information including supplementary information indicating at least a size of data recorded, as excluding the defective areas,

wherein the data is written according to a write command, the write command being generated by referring to information on the defective areas is reported-specified in advance before the real time recording so as to exclude the defective areas when the real time data is recorded on an area of the optical recording medium, and wherein the defective areas are specified based on a Defect List recorded on the Defect Management area ~~while the defective areas is not replaced with a replacement block of a spare area during the real time~~

~~recording, and the file system information includes supplementary information indicating at least a size of data recorded, as excluding the defective areas.~~

60. (Previously presented) The optical recording medium of claim 59, wherein the supplementary information is written based on the defective areas, respectively.

61. (Previously presented) The optical recording medium of claim 60, wherein the supplementary information indicates at least a size of the recorded data.

62. (Previously presented) The optical recording medium of claim 60, wherein the supplementary information further indicates a start address of the recorded data.

63. (Previously presented) The optical recording medium of claim 60, wherein the file system information is recorded on an area of the optical recording medium upon completion of the data recording or during the data recording.

64. (New) The method of claim 1, wherein the write command is sent from a host to a record/playback device.

65. (New) The method of claim 10, wherein the write command is sent from a host to a record/playback device.

66. (New) The method of claim 18, wherein the write command is sent from a host to a record/playback device.

67. (New) The method of claim 25, wherein the write command is sent from a host to a record/playback device.

68. (New) The method of claim 29, wherein the write command is sent from a host to a record/playback device.

69. (New) The method of claim 37, wherein the write command is sent from a host to a record/playback device.

70. (New) The method of claim 42, wherein the write command is received by a record/playback device from a host.

71. (New) The method of claim 47, wherein the write mode is controlled by a host when sending the data to be written to a record/playback device.

72. (New) The method of claim 52, wherein the write mode is controlled by a host when sending the data to be written to a record/playback device.

73. (New) The optical recording medium of claim 53, wherein the write command is sent from a host to a record/playback device controlling the optical recording medium.

74. (New) The optical recording medium of claim 59, wherein the write command is sent from a host to a record/playback device controlling the optical recording medium.